

CLAIM SET AS AMENDED

1. (Currently Amended) The A method for creating digital transport stream units, comprising the steps of:
 - (a) detecting program clock references contained in digital transport stream packets received from a set top box through a digital interface;
 - (b) creating the a transport time reference for each of the transport stream packet packets based upon the detected program clock references and arrival times of the correspondent corresponding transport stream packet packets; and
 - (c) creating the transport stream units by adding each of the created transport time reference references to the an associated one of the transport stream packet packets.
2. (Currently Amended) The method set forth in claim 1, wherein said step (b) creates the transport time reference of for each of the transport stream packet packets based upon an error, defined as the a difference between the time difference differences of selectively inserted program clock references and the an arrival time difference of for each of the transport stream packets containing the program clock references.
3. (Currently Amended) The method set forth in claim 2, wherein said step (b) increases or decreases the transport time reference by the a time corresponding to said error.

4. (Currently Amended) The method set forth in claim 2, wherein said step (b) creates the transport time reference for an arbitrary one of the transport stream packet packets received between two of the transport stream packets having program clock references by compensating the arrival time of the arbitrary one of the transport stream packet packets by the an amount corresponding to the a proportion of the arrival time difference between the arbitrary one of the transport stream packet packets and a first transport stream packet one of said two transport stream packets to the arrival time difference of said two transport stream packets.

5. (Currently Amended) The method set forth in claim 1, wherein said transport time reference is the reference information upon which the timing of the transmission of the transport stream packets is based when the transport stream packets are transmitted to an external device after the transport stream packets are reproduced from a storage medium.

6. (Previously Presented) The method set forth in claim 1, further comprising a step of recording the created transport stream units on a rewritable recording medium having a digital data recording format.

7. (Currently Amended) A method for creating digital transport stream units,

comprising the steps of:

- (a) storing digital transport stream packets received from a set top box through a digital interface together with their arrival times temporarily;
- (b) compensating the temporarily stored arrival time of each of the transport stream packet packets based upon ~~the a~~ time difference of program clock references and ~~the an~~ arrival time difference of the transport stream packets when more than two of the program clock references are detected from said received digital transport stream packets; and
- (c) creating transport stream units by adding each of the compensated arrival times to the associated ones of the transport stream packet packets as a transport time reference.

8. (Currently Amended) A method for creating digital transport stream units, comprising the steps of:

- (a) detecting program clock references from transport stream packets received from a set top box through a digital interface while storing the received digital transport stream packets together with their arrival times;
- (b) detecting the stored arrival times of the transport stream packets containing the detected program clock references;
- (c) comparing ~~the a~~ difference of the two program clock references detected in said step (a) with ~~the an~~ arrival time difference of the two transport stream packets detected in said step (b);

(d) compensating the stored arrival time of each of the transport stream packet packets based upon the comparison result; and

(e) creating transport stream units by adding the compensated arrival time to each of the transport stream packet packets as a transport time reference.

9. (Currently Amended) An apparatus for recording digital transport streams, comprising:

a means for detecting program clock references contained in digital transport stream packets received from a set top box through a digital interface;

a means for comparing the detected program clock references with the arrival times of the transport stream packets;

a means for creating the a transport time reference ~~of said~~ for each of said transport stream packet packets based upon the comparison result; and

a means for constructing transport stream units by adding the created transport time reference of ~~said~~ each of the transport stream packet packets to ~~the~~ an associated one of the transport stream packet packets.

10. (Currently Amended) An apparatus for recording digital transport streams, comprising:

a means for creating arrival times of digital transport stream packets received from a set

top box through a digital interface;

a means for detecting program clock references contained in the received digital transport stream packets;

a means for comparing the detected program clock references with the created arrival times;

a means for compensating the created arrival times based upon the comparison result;
and

a means for constructing transport stream units by adding ~~the a~~ compensated arrival times~~-time~~ to ~~the a~~ corresponding one of the transport stream packets as a transport time references reference.

11. (Currently Amended) The apparatus set forth in claim 10, wherein said compensating means compensates the created arrival times of the received digital transport stream packets so that ~~the difference differences~~ between the detected program clock references ~~equals are equal~~ to ~~the difference differences~~ between the arrival times of the transport stream packets containing the detected program clock references.

12. (Currently Amended) An apparatus for recording digital transport streams, comprising:

a time information extractor ~~of for~~ detecting program clock references contained in

digital transport stream packets received from a set top box through a digital interface;

a time comparator of for comparing the detected program clock references from said time information extractor with the arrival times of the transport stream packets;

a transport time generator of for creating the a transport time reference of for each of said each transport stream packet packets based upon the comparison result from said time comparator; and

a data constructor of for constructing transport stream units by adding the created transport time reference from said transport time generator of each of said each transport stream packet packets to the an associated one of the transport stream packet packets.

13. (Currently Amended) The apparatus set forth in claim 12, wherein said transport time generator creates the transport time reference of for each of the transport stream packet packets based upon an error, defined as the a difference between the time difference differences of the detected program clock references and the arrival time difference of for each of the transport stream packets containing the program clock references.

14. (Currently Amended) The apparatus set forth in claim 13, wherein said transport time generator increases or decreases the transport time reference by the a time proportional to said error.

15. (Currently Amended) The apparatus set forth in claim 13, wherein said transport time generator creates the transport time reference for an arbitrary one of the transport stream packet packets received between two of the transport stream packets having the program clock references by compensating the arrival time of the arbitrary transport stream packet by the an amount corresponding to the a proportion of the arrival time difference between the arbitrary transport stream packet and a first transport stream packet of said two transport stream packets to the arrival time difference of said two transport stream packets.

16. (Currently Amended) An apparatus for recording digital transport streams, comprising:

a transport time generator of for creating arrival times of digital transport stream packets received from a set top box through a digital interface;

a time information extractor of for detecting program clock references contained in the received digital transport stream packets;

a time comparator of for comparing the detected program clock references from said time information generator with the created arrival times from said transport time generator;

a time compensator of for compensating the created arrival times from said transport time generator based upon the comparison result of said time comparator; and

a data constructor ~~of~~ for constructing transport stream units by adding the compensated arrival times from said time compensator to the corresponding transport stream packets as transport time references.

17. (Currently Amended) The apparatus set forth in claim 16, wherein said time compensator compensates the created arrival time based upon an error, defined as ~~the a~~ difference between ~~the time difference~~ differences of the detected program clock references and the arrival time difference of each of the transport stream packets containing the program clock references.

18. (Currently Amended) The apparatus set forth in claim 17, wherein said time compensator increases or decreases the created arrival time by ~~the a~~ time proportional to said error.

19. (Currently Amended) The apparatus set forth in claim 17, wherein said time compensator ~~compensate~~ compensates the created arrival time of an arbitrary one of the transport stream ~~packet~~ packets received between two transport stream packets having the program clock references by ~~the an~~ amount corresponding to ~~the a~~ proportion of the arrival time difference between the arbitrary transport stream packet and a first transport stream

packet of said two transport stream packets to the arrival time difference of said two transport stream packets.

20. (Previously Presented) The apparatus as set forth in claim 16, wherein a clock frequency of the digital interface is 24.576 Mhz., whereas a clock frequency for recording the digital transport streams is 27 Mhz.